

Adhesive Backed Clear Vinyl for Water-Based Inkjet Printers

Properties:

| | |
|-----------------|--|
| Product Number: | KJV5001 |
| Material: | 3.2 mil Clear Calendered Vinyl |
| Adhesive: | Clear Permanent Acrylic |
| Caliper/Gauge: | 12 mil (Coating, Vinyl, Adhesive & Liner) |
| Weight: | 320 g/m ² (10.4oz/yd ²) |
| Whiteness: | 59% |
| Brightness: | 72 |
| Gloss (60°): | 50.1 (avg) |

Printer/Ink Compatibility:

Ink saturation level of this product is 250% and heavy coated paper setting in most RIPs is appropriate. Inkjet coating is designed for use primarily with dye based inks. Although pigmented inks may be used, a slight color gamut difference may be observed. Product can be printed on Endcad/Kodak (dye inks only), Hewlett-Packard DesignJet (2xxx/3xxx/5xxx), ColorSpan Displaymaker (dye inks only), Epson Stylus Pro (7xxx/9xxx), Mimaki JV4 (pigmented inks only) and Roland Hi-Fi Jet (pigmented inks only)

Ink Dry Time: Varies with type and amount of ink, relative humidity and temperature.

Environment:

| | |
|---------------------------|--|
| Printing: | 60-80° F, 50% Relative Humidity |
| Ideal Storage Conditions: | 70° F (21° C), 50% Relative Humidity, store in original packaging. |
| Handling Requirements: | Due to absorptive nature of the coating, avoid touching the coated surface with bare skin. Always wear cotton gloves when handling inkjet-coated materials. Rolls are supplied with the coated surface wound out. When rolling graphics, always roll so that the thinner material is on the outside surface of roll. |
| Life Expectancy: | Indoor - up to 6 months without lamination. |
| Shelf Life: | 6 months from ship date when stored in proper conditions. |

Finishing/Lamination: A pressure sensitive vinyl laminate is recommended, to give surface protection from dirt and abrasion. Thermal laminates should not be used. Before lamination, please allow image to dry for 24 hours.

Standard Warranty

All statements, technical information and recommendations about Kapco products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All Kapco products are sold with the understanding that the Purchaser has independently determined the suitability of such product for its purposes. Kapco products are warranted to be free from defects in material and workmanship for either one year (or the period stated on the specific product information literature in effect at time of delivery, if longer) from date of shipment if said product is properly stored and applied. It is expressly agreed and understood that Kapco's sole obligation and Purchaser's exclusive remedy under this warranty, under any other warranty, express or implied, or otherwise, shall be limited to repair or replacement of defective product without charge at Kapco's plant or at the location of product (at Kapco's election), or in the event replacement or repairs is not commercially practical, to Kapco's issuing Purchaser a credit reasonable in light of the defect in the product.

Kapco's liability for defective products shall not exceed the purchase price paid therefore by Purchaser and in no event shall Kapco be responsible for any incidental or consequential damages whether foreseeable or not, caused by defects in such product, whether such damage occurs or is discovered before or after replacement or credit, and whether or not such damage is caused by Kapco's negligence.

No express warranties and no implied warranties, whether of merchantability or fitness for any particular use, or otherwise (except as to title) other than those expressly set forth above which are made expressly in lieu of all other warranties, shall apply to products sold by Kapco. Kapco specifically disclaims and excludes all other such warranties, no waiver, alteration, addition or modification of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Kapco.